


TITANIUM
TECHNOLOGY



Aluminium Profile
2025

SURFACE



Credit photo: Cuisines Simard




TT-01-3000 Page 7

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-04-3000 Page 8

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-06-3000 Page 9

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118




TT-07-3000 Page 10

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-09-3000 Page 11

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-10-3000 Page 12

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-16-3000 Page 13

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-21-3000 Page 14

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-22-3000 Page 15

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118





Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-23-2000 Page 16




Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-24-2000 Page 17



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-25-3000 Page 18



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-32-2000 Page 19



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-38-3000 Page 20



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-40-2000 Page 21



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-40-2000-BK Page 22




Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-52-3000 Page 23



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-64-3000 Page 24






Power (W/m)	Luminous flux (lm/foot)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-65-3000 Page 25



Power (W/m)	Luminous flux (lm/foot)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-66-2000 Page 26



Power (W/m)	Luminous flux (lm/foot)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-68-3000 Page 27



Power (W/m)	Luminous flux (lm/foot)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-76-3000 Page 28



Power (W/m)	Luminous flux (lm/foot)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-80-2000 Page 29




PRODUCT BUILDER CODE

TT	-	PROFILE	-	LENGTH (inch)	-	LUMEN PACKAGE	-	COLOUR CCT	-	IP	-	VOLTAGE	-	LEAD IN (inch)	-	LEAD OUT (inch)	-	END CAP	-	CLIP	-	PSU
TT	-		-		-		-		-		-		-		-		-		-		-	
						28/6 221 lm/feet 5W/feet 28/6 H 527 lm/feet 6,25W/feet <i>*24v only</i> 28/12 456 lm/feet 9W/feet <i>*24v only</i> 35/3 45 lm/feet 1,5W/feet 35/6 120 lm/feet 3W/feet 22/15 425 lm/feet 9W/feet <i>*24v only</i> 50/3 4,5W/feet DX/24 DIGITAL DMX <i>*24V only</i>		27 2700K 30 3000K 35 3500K 40 4000K 60 6000K RE RED GR GREEN BL BLUE AM AMBER PK PINK <i>*28/6 only</i> CB CYAN <i>*28/6 only</i> OR ORANGE <i>*28/6 only</i> UV <i>*28/6 only</i> RGB <i>*50/3, 28/6 or 35/6 only</i> RGBWW <i>*50/3 only</i> RGBNW <i>*50/3 only</i> RGBCW <i>*50/3 only</i> RGBCCT <i>*50/3 only</i>		20 65		12 24		Hxxxx 12 inchs minimum DCxxxx 12 inchs minimum DCxxxx 12 inchs minimum		empty No lead out Hxxxx 12 inchs minimum DCxxxx 12 inchs minimum		NE No end cap EC With end cap		NC No Clip xC x=QTE		n/a No psu P Plug-in CV Dimmable CV-BOX Dimmable with box CV67 IP67 psu 120V No dimmagle 120v psu 347V No dimmable 347V PSU 010 0-10v PSU


For a custom color, add at the end of the manufacturer code number COLOR RAL K7. Contact your dealer about the additional cost to a special color.




- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118 ").



Size	15,2mm x 6mm x 3000mm $5/8" \times 1/4" \times 118 \frac{1}{8}"$
Lenght	3000mm $118 \frac{1}{8}"$
Internal width	11,5mm $7/16"$
Cover	Opal



Accessories




PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	01	-	3000	-	O


TT-04-3000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118 ").



Size	Ø18,4mm x 3000mm Ø¾" x 118 1/8"
Lenght	3000mm 118 1/8"
Internal width	11,3mm 7/16"
Cover	Opal



Accessories



TT-04-CLIP



TT-04-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	04	-	3000	-	O


TT-06-3000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118 ").



Size	18,4mm x 18,4mm x 3000mm $\frac{3}{4}'' \times \frac{3}{4}'' \times 118 \frac{1}{8}''$
Lenght	3000mm 118 $\frac{1}{8}''$
Internal width	14,1mm $\frac{9}{16}''$
Cover	Matte Opal PMMA Clear PMMA Black PMMA PC diffuser



Accessories



TT-06-CLITT-06-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	06	-	3000	-	O


TT-07-3000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118 ").



Size	40mm x 12mm x 3000mm 1 9/16" x 1/2" x 118 1/8"
Lenght	3000mm 118 1/8"
Internal width	11,5mm 7/16"
Cover	Opal




Accessories




PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	07	-	3000	-	O


TT-09-3000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118").



Size	30mm x 10,4mm x 3000mm $1\frac{3}{16}" \times \frac{7}{16}" \times 118\frac{1}{8}"$
Lenght	3000mm $118\frac{1}{8}"$
Internal width	11,2mm $\frac{7}{16}"$
Cover	Opal



Accessories




PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	09	-	3000	-	O


TT-10-3000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118 ").



Size	30mm x 8mm x 3000mm 1 ³ / ₁₆ " x ⁵ / ₁₆ " x 118 ¹ / ₈ "
Lenght	3000mm 118 ¹ / ₈ "
Internal width	13,2mm 1 ¹ / ₂ "
Cover	Opal



Accessories




PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	10	-	3000	-	O

TT-16-2000-O

- Aluminum profile for attaching a glass shelf of 8mm.
- Designed to cover the LED strips and diffuse the light in the glass.
- Designed to be wall mounted.
- Available in lengths 2000 mm (78³/₄").



Size	57,5mm x 58,8mm x 2000mm 2 ¹ / ₄ " x 2 ⁵ / ₁₆ " x 78 ³ / ₄ "
Length	2000mm 78 ³ / ₄ "
Internal width	12mm 1/2"
Cover	None

*Glass not include.

Accessories




PRODUCT CODE

TT	-	MODEL	-	LENGTH (mm)	-	COVER
TT	-	16	-	2000	-	O


TT-21-3000-O



- Aluminum profile with white acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").



Size	16mm x 16mm x 3000mm 5/8" x 5/8" x 118 1/8"
Lenght	3000mm 118 1/8"
Internal width	10,5mm 7/16"
Cover	Matte Opal PMMA Clear PMMA Black PMMA PC diffuser



Accessories



TT-21-CLIP



TT-21-END

PRODUCT CODE


TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	21	-	3000	-	O

TITANIUM

TECHNOLOGY

TT-22-3000-O

- Aluminum profile with clear acrylic.
- Designed to cover the LED ribbons and dissipate heat.
- Acrylic lens concentrates the light in a range of 30°
- Swivel attachment to guide the light.
- Available in lengths 3000 mm (118¹/₈").




Size	20,4mm x 17,3mm x 3000mm 1 ³ / ₁₆ " x 1 ¹ / ₁₆ " x 118 ¹ / ₈ "
------	---

Lenght	3000mm 118 ¹ / ₈ "
--------	---

Internal width	12,8mm 1 ¹ / ₂ "
----------------	---

Cover	Clear, 30° lens
-------	-----------------



Accessories



TT-22-CLIP



TT-22-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	22	-	3000	-	O


TT-23-2000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2000 mm ($78\frac{3}{4}$ ").



Size	48,5mm x 16,7mm x 2000mm $1\frac{15}{16}$ " x $1\frac{11}{16}$ " x $78\frac{3}{4}$ "
Lenght	2000mm $78\frac{3}{4}$ "
Internal width	2 x 12,2mm 2 x $1\frac{1}{2}$ "
Cover	Matte Opal PMMA Clear PMMA Black PMMA PC diffuser



Accessories



TT-23-CLIP



TT-23-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	23	-	2000	-	O


TT-24-2000-O



- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2000 mm ($78\frac{3}{4}$ ").



Size	44mm x 17,6mm x 2000mm $1\frac{3}{4}$ " x $1\frac{11}{16}$ " x $78\frac{3}{4}$ "
Lenght	2000mm $78\frac{3}{4}$ "
Internal width	12,7mm $\frac{1}{2}$ "
Cover	Matte Opal PMMA Clear PMMA Black PMMA PC diffuser



Accessories



TT-24-CLIP



TT-24-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	24	-	2000	-	O


TT-25-3000-O



- Aluminum profile with white acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈ ").



Size	17,3mm x 14,6mm x 3000mm 11/16" x 9/16" x 118 1/8"
Lenght	3000mm 118 1/8"
Internal width	12,8mm 1/2"
Cover	Matte Opal PMMA Clear PMMA Black PMMA PC diffuser



Accessories





PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	25	-	3000	-	O

TT-32-2000-O

- Aluminum profile with opal acrylic.
- Designed in flexible aluminum to conceal LED ribbons and dissipate heat on curved surfaces.
- Available in lengths 2000 mm (78³/₄ ").



Size	18mm x 5,3mm x 2000mm $11/16" \times 3/16" \times 78^{3/4}"$
Lenght	2000mm $78^{3/4}"$
Internal width	12mm $1/2"$
Cover	Opal PC diffuser

Accessories




PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	32	-	2000	-	O


TT-38-3000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").



Size	17mm x 8mm x 3000mm 11/16" x 5/16" x 118 ¹ / ₈ "
Lenght	3000 mm 118 ¹ / ₈ "
Internal width	12mm 1/2"
Cover	Matte Opal PMMA Clear PMMA Black PMMA PC diffuser



Accessories




PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	38	-	3000	-	O


TT-40-2000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2000 mm (78³/₄").



Size	23,5mm x 15mm x 2000mm $15/16" \times 5/8" \times 78^{3/4}"$
Lenght	2000mm $78^{3/4}"$
Internal width	20,4mm $13/16"$
Cover	PC diffused



Accessories



TT-40-CLIP



TT-40-END



TT-40-SUSP


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	40	-	2000	-	O


TT-40-2000-O-BK



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2000 mm (78³/₄").



Size	23,8mm x 16,7mm x 2000mm $15\frac{15}{16}'' \times 11\frac{11}{16}'' \times 78\frac{3}{4}''$
Lenght	2000mm $78\frac{3}{4}''$
Internal width	20,8mm $13\frac{13}{16}''$
Cover	PC diffused



Accessories



TT-40-CLIP



TT-40-END-BK




TT-40-SUSP

PRODUCT CODE					
TT	MODEL	LENGHT (mm)	COVER	FINISH	
TT	40	2000	O	BK	

TT-52-3000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").




Size 16mm x 16mm x 3000mm
5/8" x 5/8" x 118¹/₈"

Lenght 3000mm
118¹/₈"

Internal width 10,5mm
7/16"

Cover Matte opal PMMA



Accessories



TT-52-CLIP



TT-52-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	52	-	3000	-	O

TT-64-3000-O



- Aluminum profile with smoked acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").



Size	13mm x 20,5mm x 3000mm $1\frac{1}{2}'' \times 13\frac{1}{16}'' \times 118\frac{1}{8}''$
Lenght	3000mm $118\frac{1}{8}''$
Internal width	11mm $7\frac{7}{16}''$
Finish	BK - Black (n/a) Grey
Cover	PC diffused


*Glass not include.

PRODUCT CODE


TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	64	-	3000	-	O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm ($118\frac{1}{8}$ ").



Size	31mm x 20mm x 3000mm $1\frac{1}{4}$ " x $\frac{13}{16}$ " x $118\frac{1}{8}$ "
Lenght	3000mm $118\frac{1}{8}$ "
Internal width	2 x 12,6mm 2 x $\frac{1}{2}$ "
Finish	BK - Black (n/a) Grey
Cover	PC diffused




PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	65	-	3000	-	O

TT-66-2000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2000 mm ($78\frac{3}{4}$ ").




Size	31,6mm x 18,5mm x 2000mm $7\frac{7}{16}$ " x $3\frac{3}{4}$ " x $78\frac{3}{4}$ "
------	--

Lenght	2000mm $78\frac{3}{4}$ "
--------	-----------------------------

Internal width	12,3mm $\frac{1}{2}$ "
----------------	---------------------------

Cover	PC diffused
-------	-------------



Accessories



TT-66-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	66	-	2000	-	O

TT-68-3000-O



- Aluminum profile with white acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").




Size 23,5mm x 10mm x 3000mm
 $15/16'' \times 3/8'' \times 118\frac{1}{8}''$

Lenght 3000mm
 $118\frac{1}{8}''$

Internal width 20mm
 $13/16''$

Cover Matte opal PMMA



Accessories



TT-68-CLIP




TT-68-END

PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	68	-	3000	-	O

TT-76-3000-O




Size	7,8mm x 9mm x 3000mm $\frac{5}{16}'' \times \frac{3}{8}'' \times 118\frac{1}{8}''$
Lenght	3000mm $118\frac{1}{8}''$
Internal width	5,5mm $\frac{1}{4}''$
Cover	PC

Accessories



TT-76-CLIP




TT-76-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	76	-	3000	-	O


TT-80-2000-O



- .Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2000 mm (78³/₄").



Size	20,7mm x 51mm x 2000mm ³ / ₁₆ " x 2" x 78 ³ / ₄ "
Lenght	2000mm 78 ³ / ₄ "
Internal width	13,5mm ⁹ / ₁₆ "
Finish	White
Cover	PC



Accessories



TT-80-EXT



TT-80-EXT-90



TT-80-END

PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	80	-	2000	-	O

RECESSED



Credit photo: Christian Marcoux



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-02-3000 Page 33



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-14-3000 Page 34



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-17-2500 Page 35



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-18-2500 Page 36



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-19-2000 Page 37




Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-39-3000 Page 38



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-49-2000 Page 39



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-50-2000 Page 40



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-69-3000 Page 41




TT-74-3000 Page 42

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-77-3000 Page 43

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-79-3000 Page 44

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



PRODUCT BUILDER CODE


[illegible]

For a custom color, add at the end of the manufacturer code number COLOR RAL K7. Contact your dealer about the additional cost to a special color.


TT-02-3000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118 1/8").



Size	15,2mm x 4,8mm x 3000mm $\frac{5}{8}" \times \frac{3}{16}" \times 118 \frac{1}{8}"$
Lenght	3000mm $118 \frac{1}{8}"$
Internal width	11,5mm $\frac{7}{16}"$
Cover	Opal



Accessories



TT-02-CLIP



TT-02-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	02	-	3000	-	O


TT-14-3000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").



Size	17,3mm x 12,9mm x 3000mm 11/16" x 1/2" x 118 ¹ / ₈ "
Lenght	3000mm 118 ¹ / ₈ "
Internal width	12,8mm 1/2"
Cover	Matte Opal PMMA Clear PMMA Black PMMA PC diffuser



Accessories




PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	14	-	3000	-	O

TT-17-2500-O



- Aluminum profile with white acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2500 mm (98³/₈ ").




Size	35mm x 35mm x 2500mm 1 ³ / ₈ " x 1 ³ / ₈ " x 98 ³ / ₈ "
------	--

Lenght	2500mm 98 ³ / ₈ "
--------	--

Internal width	25,7mm 1"
----------------	--------------

Cover	PC diffused
-------	-------------



Accessories



TT-17-SNAP




TT-17-L



TT-17-T




TT-17-X



TT-17-I



TT-17-END



TT-17-EXT



TT-17-EXT-90



TT-17-EXT-90IL



TT-17-EXT-60




TT-17-EXT-120


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	17	-	2500	-	O

TT-18-2500-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2500 mm (98³/₈ ").




Size 123mm x 35mm x 2500mm
4⁷/₈" x 1¹/₂" x 98³/₈"

Length 2500mm
98³/₈"

Internal width 77,5mm
3"

Cover PC diffuse



Accessories



TT-18-SNAP



TT-18-L



TT-18-T




TT-18-X



TT-18-I



TT-18-END



TT-18-EXT



TT-18-EXT-90



TT-18-EXT-90IL



TT-18-EXT-60



TT-18-EXT-120


PRODUCT CODE

TT	-	MODEL	-	LENGTH (mm)	-	COVER
TT	-	18	-	2500	-	O


TT-19-2000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2000 mm ($78\frac{3}{4}$ ").



Size	101mm x 50mm x 2000mm 4" x 2" x $78\frac{3}{4}$ "
Lenght	2000mm $78\frac{3}{4}$ "
Internal width	2 x 12mm 2 x $1\frac{1}{2}$ "
Cover	Semi clear PMMA




Accessories




PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	19	-	2000	-	O



TT-39-3000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").



Size	23,3mm x 5,9mm x 3000mm ¹⁵ / ₁₆ " x ¹ / ₄ " x 118 ¹ / ₈ "
Lenght	3000mm 118 ¹ / ₈ "
Internal width	12mm ¹ / ₂ "
Cover	Matte Opal PMMA Clear PMMA Black PMMA PC diffuser




Accessories




PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	39	-	3000	-	O


TT-49-2000-O



- Aluminum profile with white acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2000 mm ($78\frac{3}{4}$ ").



Size	29,4 x 14,2 x 2000 mm $1\frac{3}{16}$ " x $\frac{9}{16}$ " x $78\frac{3}{4}$ "
Lenght	2000 mm $78\frac{3}{4}$ "
Internal width	8,8 mm $\frac{3}{8}$ "
Cover	PC diffused



Accessories



TT-49-SNAP



TT-49-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	49	-	2000	-	O


TT-50-2000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2000 mm (78³/₄").



Size	19mm x 13,6mm x 2000mm 3/4" x 9/16" x 78 ³ / ₄ "
Lenght	2000mm 78 ³ / ₄ "
Internal width	12mm 1/2"
Cover	PC diffused



Accessories



TT-50-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	50	-	2000	-	O


TT-69-3000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").



Size	30,5mm x 10mm x 3000mm 1 ³ / ₁₆ " x 3/ ₈ " x 118 ¹ / ₈ "
Lenght	3000mm 118 ¹ / ₈ "
Internal width	20mm 1 ³ / ₁₆ "
Cover	Matte Opal PMMA



Accessories




TT-69-END

PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	69	-	3000	-	O

TT-74-3000-O



Size	13,7mm x 9,3mm x 3000mm $\frac{9}{16}'' \times \frac{3}{8}'' \times 118\frac{1}{8}''$
Lenght	3000mm $118\frac{1}{8}''$
Internal width	11,7mm $\frac{7}{16}''$
Cover	Silicone

Accessories




TT-74-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	74	-	3000	-	O


TT-77-3000-O



- Designed to use with the TT-2025FR-L600 LED strip.
- Available in lengths 3000 mm ($118\frac{1}{8}$ ").



Size	9,5mm x 9mm x 3000mm $\frac{3}{8}$ " x $11\frac{1}{32}$ " x $118\frac{1}{8}$ "
Lenght	3000mm $118\frac{1}{8}$ "
Internal width	8mm $\frac{5}{16}$ "
Finish	AL - Aluminium CL - Charcoal Grey BK - Black
Cover	Matte Opal PMMA



Accessories



TT-77-CLIP



TT-77-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER	-	FINISH
TT	-	77	-	3000	-	O	-	BK
TT	-	77	-	3000	-	O	-	

TT-79-3000-O



- Designed to use with the TT-2025FR-L600 LED strip.
- Available in lengths 3000 mm (118¹/₈").



Size	10mm x 9,8mm x 3000mm ³ / ₈ " x ³ / ₈ " x 118 ¹ / ₈ "
Lenght	3000mm 118 ¹ / ₈ "
Finish	AL - Aluminium BK - Black WH- White
Cover	PC

Accessories



PRODUCT CODE								
TT	-	MODEL	-	LENGHT (mm)	-	COVER	-	FINISH
TT	-	79	-	3000	-	O	-	BK
TT	-	79	-	3000	-	O	-	

PENDANT



Credit photo: Volkswagen St-Nicolas



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-13-3000 Page 51



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-15-3000 Page 52



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-15-3000-BK Page 53




Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-20-2000 Page 54



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-31-2500 Page 55



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-37-2500 Page 56



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-46-2500 Page 57



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-47-2500 Page 58



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-48-2500 Page 59



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-48-2500-BK Page 60





Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-53-2000 Page 61




Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-54-2000-BK Page 62




Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-54-2000-WH Page 63




Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
-	-	90	2700 ~ 6000	Ø 23 5/8

TT-R25-600 Page 64




Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
-	-	90	2700 ~ 6000	Ø 35 7/16

TT-R25-900 Page 65



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
-	-	90	2700 ~ 6000	Ø 50

TT-R25-1270 Page 66




Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
-	-	90	2700 ~ 6000	Ø 70 7/8

TT-R25-1800 Page 67



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
-	-	90	2700 ~ 6000	Ø 23 5/8

TT-R30-600 Page 68




Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
-	-	90	2700 ~ 6000	Ø 35 7/16

TT-R30-900 Page 69



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
-	-	90	2700 ~ 6000	Ø 47 1/4


TT-R30-1200 Page 70






TT-R50-900 Page 71

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
-	-	90	2700 ~ 6000	Ø 35 7/16




TT-R50-1270 Page 72

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
-	-	90	2700 ~ 6000	Ø 50



TT-R50-1800 Page 73

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
-	-	90	2700 ~ 6000	Ø 70 7/8



TT-CANOPY-01 Page 74

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
-	-	-	-	Ø 11



TT-CANOPY-02 Page 75

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
-	-	-	-	Ø 13



TT-CANOPY-03 Page 76

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
-	-	-	-	-



TT-CANOPY-04 Page 77

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
-	-	-	-	-



PRODUCT BUILDER CODE


TT	-	PROFILE	-	LENGTH (inch)	-	LUMEN PACKAGE	-	CLOUR CCT	-	IP	-	VOLTAGE	-	LEAD IN (inch)	-	LEAD OUT (inch)	-	END CAP	-	CLIP	-	PSU
TT	-		-		-		-		-		-		-		-		-		-		-	
						28/6 221 lm/feet 5W/feet		27 2700K		20		12		Hxxxx 12 inchs minimum		empty No lead out		NE No end cap		NC No Clip		n/a No psu
						28/6 H 527 lm/feet 6,25W/feet *24v only		30 3000K		65		24		DCxxxx 12 inchs minimum		Hxxxx 12 inchs minimum		EC With end cap		xC x=QTE		P Plug-in
						28/12 456 lm/feet 9W/feet *24v only		35 3500K						DCxxxx 12 inchs minimum								CV Dimmable
						35/3 45 lm/feet 1,5W/feet		40 4000K														CV-BOX Dimmable with box
						35/6 120 lm/feet 3W/feet		60 6000K														CV67 IP67 psu
						22/15 425 lm/feet 9W/feet *24v only		RE RED														120V No dimmable 120v psu
						50/3 4,5W/feet		GR GREEN														347V No dimmable 347V PSU
						DX/24 DIGITAL DMX *24V only		BL BLUE														010 0-10v PSU
								AM AMBER														
								PK PINK *28/6 only														
								CB CYAN *28/6 only														
								OR ORANGE *28/6 only														
								UV *28/6 only														
								RGB *50/3, 28/6 or 35/6 only														
								RGBWW *50/3 only														
								RGBNW *50/3 only														
								RGBCW *50/3 only														
								RGBCCT *50/3 only														

For a custom color, add at the end of the manufacturer code number COLOR RAL K7. Contact your dealer about the additional cost to a special color.

TT-13-3000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈ ").



Size

75mm x 35mm x 3000mm
3" x 1³/₈" x 118¹/₈"

Length


3000mm
118¹/₈"

Internal width

64mm
2¹/₂"

Cover

PC diffused



Accessories




TT-13-END




TT-13-SUSP



TT-13-L



TT-13-T




TT-13-X



TT-13-EXT



TT-13-EXT-90



TT-13-EXT-90IL



TT-13-EXT-60



TT-13-EXT-120


PRODUCT CODE

TT	-	MODEL	-	LENGTH (mm)	-	COVER
TT	-	13	-	3000	-	O


TT-15-3000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").



Size	20,3mm x 27mm x 3000mm ¹³ / ₁₆ " x 1 ¹ / ₁₆ " x 118 ¹ / ₈ "
Lenght	3000mm 118 ¹ / ₄ "
Internal width	16,8mm ¹¹ / ₁₆ "
Cover	Matte opal PMMA



Accessories



TT-15-CLIP



TT-15-SUSP



TT-15-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	15	-	3000	-	O


TT-15-3000-O-BK



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").



Size	20,3mm x 27mm x 3000mm $13/16" \times 1 1/16" \times 118 1/8"$
Lenght	3000mm $118 1/4"$
Internal width	16,8mm $11/16"$
Cover	Matte opal PMMA
Finish	Black



Accessories



TT-15-CLIP



TT-15-SUSP



TT-15-END-BK


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER	-	FINISH
TT	-	15	-	3000	-	O	-	BK

TT-20-2000-O



- Aluminum profile with white acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2000 mm (78³/₄ ").




Size $\varnothing 20,5\text{mm} \times 2000\text{mm}$
 $\varnothing 13/16" \times 78^{3/4}"$

Lenght 2000mm
78³/₄"

Internal width 12mm
1/2"

Cover Matte opal PMMA



Accessories



TT-20-CLIP



TT-20-SUSP




TT-20-END

PRODUCT CODE


TT - MODEL - LENGHT (mm) - COVER

TT - 20 - 2000 - O

TT-31-2500-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2500 mm ($98\frac{3}{8}$ ").



Size 151mm x 23mm x 2500mm
 $5\frac{15}{16}$ " x $\frac{7}{8}$ " x $98\frac{3}{8}$ "

Lenght 2500mm
 $98\frac{3}{8}$ "

Internal width 3 x 27mm
3 x $1\frac{1}{16}$ "

Cover PC frosted



Accessories



TT-31-SUSP



TT-31-END



PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	31	-	2500	-	O

TT-37-2500-O




- Extruded aluminum with opal acrylic cylinder.
- Available in length of 2500 mm (98³/₈ ").



Size	Ø100 mm x 2500 mm 3 ¹⁵ / ₁₆ " x 98 ³ / ₈ "
Lenght	2500mm 98 ³ / ₈ "
Internal width	43mm 1 ¹¹ / ₁₆ "
Cover	PC diffused

Accessories




PRODUCT CODE						
TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	37	-	2500	-	O


TT-46-2500-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2500 mm ($98\frac{3}{8}$ ").



Size	75mm x 50mm x 2500mm $2\frac{15}{16}$ " x $1\frac{15}{16}$ " x $98\frac{3}{8}$ "
Lenght	2500mm $98\frac{3}{8}$ "
Internal width	29,9mm $1\frac{3}{16}$ "
Cover	PC frosted



Accessories

PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	46	-	2500	-	O



TT-46-CLIP



TT-46-SUSP



TT-46-SNAP



TT-46-
CABLE




TT-46-END

TT-47-2500-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2500 mm (98³/₈").



Size	80mm x 38mm x 2500mm 3 ¹ / ₈ " x 1 ¹ / ₂ " x 98 ³ / ₈ "
Lenght	2500mm 98 ³ / ₈ "
Internal width	34,5mm 1 ³ / ₈ "
Cover	PC diffused



Accessories



TT-47-SUSP



TT-47-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	47	-	2500	-	O

TT-48-2500-O



- Aluminum profile with white acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2500 mm ($98\frac{3}{8}$ ").




Size 35mm x 35mm x 2500mm
 $1\frac{3}{8}$ " x $1\frac{3}{8}$ " x $98\frac{3}{8}$ "

Lenght 2500mm
 $98\frac{3}{8}$ "

Internal width 2,57mm
1"

Cover PC diffused




Accessories




TT-48-SUSP




TT-48-CLIP



TT-48-L



TT-48-T



TT-48-X




TT-48-I



TT-48-EXT



TT-48-EXT-90



TT-48-EXT-90IL



TT-48-EXT-60



TT-48-EXT-120




TT-48-END

PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	48	-	2500	-	O


TT-48-2500-O-BK



- Aluminum profile with white acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2500 mm (98³/₈ ").



Size	35mm x 35mm x 2500mm 1 ³ / ₈ " x 1 ³ / ₈ " x 98 ³ / ₈ "
Lenght	2500mm 98 ³ / ₈ "
Internal width	25,7mm 1"
Cover	PC diffused
Finish	BK-Black

Accessories



 TT-48-SUSP-BK	 TT-48-CLIP	 TT-48-L-BK	 TT-48-T-BK	 TT-48-X-BK	 TT-48-I-BK
 TT-48-EXT	 TT-48-EXT-90	 TT-48-EXT-90IL	 TT-48-EXT-60	 TT-48-EXT-120	 TT-48-END-BK


PRODUCT CODE

TT	MODEL	LENGHT (mm)	COVER	FINISH
TT	50	2000	O	BK


TT-53-2000-O



- Aluminum profile with white acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2000 mm (78³/₄ ").



Size	25,4mm x 28mm x 2000mm 1" x 1 ¹ / ₈ " x 78 ³ / ₄ "
Lenght	2000mm 78 ³ / ₄ "
Internal width	22,8mm 7/8"
Cover	PC diffused



Accessories



TT-53-CLIP



TT-53-SUSP





TT-53-END

PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	53	-	2000	-	O

TT-54-2000-O-BK

- Aluminum profile with white acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2000 mm (78³/₄ ").




Size	25mm x 25mm x 2000mm 1" x 1" x 78 ³ / ₄ "
------	--

Lenght	2000mm 78 ³ / ₄ "
--------	--

Internal width	13,2mm 1/2"
----------------	----------------

Cover	PC diffused
-------	-------------



Accessories



TT-54-CLIP



TT-54-SUSP




TT-54-END-BK

PRODUCT CODE


TT	-	MODEL	-	LENGHT (mm)	-	COVER	-	FINISH
TT	-	54	-	2000	-	O	-	BK

TT-54-2000-O-WH

- Aluminum profile with white acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2000 mm (78³/₄ ").



Size	25mm x 25mm x 2000mm 1" x 1" x 78 ³ / ₄ "
Length	2000mm 78 ³ / ₄ "
Internal width	13,2mm 1/2"
Cover	PC diffused



Accessories



TT-54-CLIP



TT-54-SUSP







TT-54-END-WH

PRODUCT CODE

TT	-	MODEL	-	LENGTH (mm)	-	COVER	-	FINISH
TT	-	54	-	2000	-	O	-	WH

TT-R25-600



Size	25,4mm x 25,4mm x Ø 600mm 1" x 1" x 23 ⁵ / ₈ "
Diameter	Ø 600mm 23 ⁵ / ₈ "
Internal width	14,1mm 9/16"





Accessories and
power supply included



PRODUCT CODE

TT	-	MODEL	-	DIAMETER (mm)
TT	-	R25	-	600

TT-R25-900



Size	25,4mm x 25,4mm x Ø 900mm 1" x 1" x 35 ⁷ / ₁₆ "
------	--

Diameter	Ø 900mm 35 ⁷ / ₁₆ "
----------	--

Internal width	14,1mm 9 ⁹ / ₁₆ "
----------------	--


Accessories and power supply included



TT-R25-LED



TT-R25-SUSP







TT-R25-EXT

PRODUCT CODE

TT	-	MODEL	-	DIAMETER (mm)
TT	-	R25	-	900

TT-R25-1270







Size	25,4mm x 25,4mm x Ø 1270mm 1" x 1" x 50"
Diameter	Ø 1270mm 50"
Internal width	14,1mm 9/16"

Accessories and
power supply included



PRODUCT CODE			
TT	-	MODEL	-
TT	-	R25	-
			DIAMETER (mm)
			1270

TT-R25-1800



Size	25,4mm x 25,4mm x Ø 1800mm 1" x 1" x 70 ⁷ / ₈ "
Diameter	Ø 1800mm 70 ⁷ / ₈ "
Internal width	14,1mm 9/16"

Accessories and power supply included



TT-R25-LED



TT-R25-SUSP







TT-R25-EXT

PRODUCT CODE

TT	-	MODEL	-	DIAMETER (mm)
TT	-	R25	-	1800

TT-R30-600



Accessories and
power supply included







Size	12mm x 30mm x Ø 600mm 1/2" x 1 3/16" x 23 5/8"
Diameter	Ø 600mm 23 5/8"
Internal width	10,5mm 7/16"

PRODUCT CODE

TT	-	MODEL	-	DIAMETER (mm)
TT	-	R30	-	600

TT-R30-900



Size	12mm x 30mm x Ø 900mm 1/2" x 1 3/16" x 35 7/16"
Diameter	Ø 900mm 35 7/16"
Internal width	10,5mm 7/16"

Accessories and power supply included







TT-R30-SUSP

PRODUCT CODE

TT	-	MODEL	-	DIAMETER (mm)
TT	-	R30	-	900

TT-R30-1200



Size	12mm x 30mm x Ø 1200mm 1/2" x 1 3/16" x 47 1/4"
------	--

Diameter	Ø 1200mm 47 1/4"
----------	---------------------

Internal width	10,5mm 7/16"
----------------	-----------------





Accessories and
power supply included



PRODUCT CODE

TT	-	MODEL	-	DIAMETER (mm)
TT	-	R30	-	1200

TT-R50-900



Size	53,6mm x 60,4mm x Ø 900mm 2 ¹ / ₈ " x 2 ³ / ₈ " x 35 ⁷ / ₁₆ "
Diameter	Ø 900mm 35 ⁷ / ₁₆ "
Internal width	41,1mm 1 ⁵ / ₈ "

Accessories and power supply included



TT-R50-LED



TT-R50-SUSP



TT-R50-EXT







TT-R50-CLIP

PRODUCT CODE

TT	-	MODEL	-	DIAMETER (mm)
TT	-	R50	-	900

TT-R50-1270



Size	53,6mm x 60,4mm x Ø 1270mm 2 ¹ / ₈ " x 2 ³ / ₈ " x 50"
Diameter	Ø 1270mm 50"
Internal width	41,1mm 1 ⁵ / ₈ "

Accessories and power supply included



TT-R50-LED



TT-R50-SUSP



TT-R50-EXT







TT-R50-CLIP

PRODUCT CODE

TT	-	MODEL	-	DIAMETER (mm)
TT	-	R50	-	1270

TT-R50-1800



Size	53,6mm x 60,4mm x Ø 1800mm 2 ¹ / ₈ " x 2 ³ / ₈ " x 70 ⁷ / ₈ "
Diameter	Ø 1800mm 70 ⁷ / ₈ "
Internal width	41,1mm 1 ⁵ / ₈ "

Accessories and power supply included



TT-R50-LED



TT-R50-SUSP





TT-R50-EXT



TT-R50-CLIP

PRODUCT CODE



TT	-	MODEL	-	DIAMETER (mm)
TT	-	R50	-	1800



Size	41mm x Ø 279,4mm 1 ⁵ / ₈ " x 11"
Diameter	Ø 279,4mm 11"
Internal width	254mm 10"

PRODUCT CODE

TT	-	TYPE	-	MODEL
TT	-	CANOPY	-	01



Size	41mm x Ø 330,2mm 1 ⁵ / ₈ " x 13"
------	---

Diameter	Ø 330,2mm 13"
----------	------------------




Internal width	Ø 304,4mm 12"
----------------	------------------

PRODUCT CODE

TT	-	TYPE	-	MODEL
TT	-	CANOPY	-	02



Size	60mm x 150mm x 380mm 2 3⁄8" x 5 7⁄8" x 1'-3"
Internal width	120mm x 350mm 4 3⁄4" x 1'-1 3⁄4"



PRODUCT CODE

TT	-	TYPE	-	MODEL
TT	-	CANOPY	-	03




Size

60mm x 150mm x 730mm
2 ³/₈" x 5 ⁷/₈" x 2'-4 ³/₄"

Internal width

120mm x 700mm
4 ³/₄" x 2'-3 ¹/₂"



PRODUCT CODE

TT - TYPE - MODEL

TT - CANOPY - 04

BLACK SHADOW SERIES



Credit photo: Cuisines Simard




TT-55-3000-BK Page 81

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118




TT-56-3000-BK Page 82

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-57-3000-BK Page 83

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-58-3000-BK Page 84

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-59-3000-BK Page 85

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-60-3000-BK Page 86

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118




TT-61-3000-BK Page 87

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118




TT-62-3000-BK Page 88

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-63-3000-BK Page 89

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118




TT-73-3000-BK Page 90

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-74-3000-O-BK Page 91

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-75-3000-O-BK Page 92

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



PRODUCT BUILDER CODE

TT	-	PROFILE	-	LENGTH (inch)	-	LUMEN PACKAGE	-	COLOUR CCT	-	IP	-	VOLTAGE	-	LEAD IN (inch)	-	LEAD OUT (inch)	-	END CAP	-	CLIP	-	PSU
TT	-		-		-		-		-		-		-		-		-		-		-	

28/6
221 lm/feet
5W/feet

28/6 H
527 lm/feet
6,25W/feet
*24v only

28/12
456 lm/feet
9W/feet
*24v only

35/3
45 lm/feet
1,5W/feet

35/6
120 lm/feet
3W/feet

22/15
425 lm/feet
9W/feet
*24v only

50/3
4,5W/feet

DX/24
DIGITAL DMX
*24V only

27
2700K

30
3000K

35
3500K

40
4000K

60
6000K

RE
RED

GR
GREEN

BL
BLUE

AM
AMBER

PK
PINK
*28/6 only

CB
CYAN
*28/6 only

OR
ORANGE
*28/6 only

UV
*28/6 only

RGB
*50/3, 28/6 or
35/6 only

RGBWW
*50/3 only

RGBNW
*50/3 only

RGBCW
*50/3 only

RGBCCT
*50/3 only

20

65

12

24

Hxxxx
12 inch
minimum

DCxxxx
12 inch
minimum

empty
No lead out

Hxxxx
12 inch
minimum

DCxxxx
12 inch
minimum

NE
No end
cap

EC
With end
cap

NC
No Clip

xC
x=QTE

n/a
No psu

P
Plug-in

CV
Dimmable

CV-BOX
Dimmable with box

CV67
IP67 psu

120V
No dimmable
120v psu

347V
No dimmable
347V PSU


010
0-10v PSU

For a custom color, add at the end of the manufacturer code number COLOR RAL K7. Contact your dealer about the additional cost to a special color.

TT-55-3000-O-BK



- Aluminum profile with smoked acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").



Size	17mm x 8mm x 3000mm 1 ¹ / ₁₆ " x 5 ⁵ / ₁₆ " x 118 ¹ / ₈ "
Length	3000mm 118 ¹ / ₈ "
Internal width	12mm 1 ¹ / ₂ "
Cover	Smoked Matte opal PMMA Clear PMMA PC diffused
Finish	BK-Black

Accessories



TT-55-CLIP




TT-55-END


PRODUCT CODE

TT	-	MODEL	-	LENGTH (mm)	-	COVER	-	FINISH
TT	-	55	-	3000	-	O	-	BK

TT-56-3000-O-BK



- Aluminum profile with smoked acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").



Size	23,3mm x 8mm x 3000mm 1 ⁵ / ₁₆ " x 5/ ₁₆ " x 118 ¹ / ₈ "
------	--

Lenght	3000mm 118 ¹ / ₈ "
--------	---

Internal width	12mm 1/ ₂ "
----------------	---------------------------

Cover	Smoked Matte opal PMMA Clear PMMA PC diffused
-------	--

Finish	BK-Black
--------	----------

Accessories



TT-56-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER	-	FINISH
TT	-	56	-	3000	-	O	-	BK

TT-57-3000-O-BK



- Aluminum profile with smoked acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").



Size	17mm x 14,6mm x 3000mm $11/16" \times 9/16" \times 118^{1/8}"$
Lenght	3000mm $118^{1/8}"$
Internal width	12,8mm $1/2"$
Cover	Smoked Matte opal PMMA Clear PMMA PC diffused
Finish	BK-Black

Accessories



TT-57-CLIP



TT-57-END


PRODUCT CODE

TT	-	MODEL	-	LENGTH (mm)	-	COVER	-	FINISH
TT	-	57	-	3000	-	O	-	BK

TT-58-3000-O-BK



- Aluminum profile with smoked acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").



Size	23,6mm x 14,6mm x 3000mm $15/16" \times 9/16" \times 118^{1/8}"$
Lenght	3000mm $118^{1/8}"$
Internal width	12,8mm $1/2"$
Cover	Smoked Matte opal PMMA Clear PMMA PC diffused
Finish	BK-Black

Accessories



TT-58-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER	-	FINISH
TT	-	58	-	3000	-	O	-	BK

TT-59-3000-O-BK



- Aluminum profile with smoked acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").



Size	16mm x 16mm x 3000mm $\frac{5}{8}" \times \frac{5}{8}" \times 118\frac{1}{8}"$
Lenght	3000mm $118\frac{1}{8}"$
Internal width	10,5mm $\frac{7}{16}"$
Cover	Smoked Matte opal PMMA Clear PMMA PC diffused
Finish	BK-Black

Accessories



TT-59-CLIP



TT-59-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER	-	FINISH
TT	-	59	-	3000	-	O	-	BK

TT-60-3000-O-BK



- Aluminum profile with smoked acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").



Size	18,5mm x 18,5mm x 3000mm 3/4" x 3/4" x 118 ¹ / ₈ "
Lenght	3000mm 118 ¹ / ₈ "
Internal width	12mm 1/2"
Cover	Smoked Matte opal PMMA Clear PMMA PC diffused
Finish	BK-Black

Accessories



TT-60-CLIP




TT-60-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER	-	FINISH
TT	-	60	-	3000	-	O	-	BK

TT-61-3000-O-BK



- Aluminum profile with smoked acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").



Size	35mm x 37,5mm x 3000mm 1 ³ / ₈ " x 1 ¹ / ₂ " x 118 ¹ / ₈ "
Lenght	3000mm 118 ¹ / ₈ "
Internal width	30,6mm 1 ³ / ₁₆ "
Cover	Smoked PC diffused
Finish	BK-Black


Accessories



TT-61-CLIP



TT-61-SUSP



TT-61-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER	-	FINISH
TT	-	61	-	3000	-	O	-	BK


TT-62-3000-O-BK



- Aluminum profile with smoked acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").



Size	49mm x 37,5mm x 3000mm 1 ¹⁵ / ₁₆ " x 1 ¹ / ₂ " x 118 ¹ / ₈ "
Lenght	3000mm 118 ¹ / ₈ "
Internal width	30,6mm 1 ³ / ₁₆ "
Cover	Smoked PC diffused
Finish	BK-Black



Accessories




PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER	-	FINISH
TT	-	62	-	3000	-	O	-	BK

TT-63-3000-O-BK

- Aluminum profile with smoked acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈").



Size	50mm x 75mm x 3000mm 1 ¹⁵ / ₁₆ " x 2 ¹⁵ / ₁₆ " x 118 ¹ / ₈ "
Lenght	3000mm 118 ¹ / ₈ "
Internal width	28,7mm 1 ¹ / ₈ "
Cover	Smoked PC diffused
Finish	BK-Black

Accessories

PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER	-	FINISH
TT	-	63	-	3000	-	O	-	BK



TT-63-CLIP



TT-63-SUSP



TT-63-SNAP




TT-63-CABLE



TT-63-END

TT-74-3000-O-BK



Size	13,7mm x 9,3mm x 3000mm $\frac{9}{16}'' \times \frac{3}{8}'' \times 118\frac{1}{8}''$
------	--

Lenght	3000mm $118\frac{1}{8}''$
--------	------------------------------

Internal width	11,7mm $\frac{7}{16}''$
----------------	----------------------------

Cover	Silicone
-------	----------

Accessories




TT-74-END-BK

PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER	-	FINISH
TT	-	74	-	3000	-	O	-	BK

TT-75-3000-O-BK



Size	15mm x 10mm x 3000mm $\frac{5}{8}" \times \frac{3}{8}" \times 118\frac{1}{8}"$
Lenght	3000mm $118\frac{1}{8}"$
Internal width	10mm $\frac{3}{8}"$
Cover	PMMA

Accessories




TT-75-END-BK

PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER	-	FINISH
TT	-	75	-	3000	-	O	-	BK

TT-73-3000-O-BK



Size	15mm x 12,5mm x 3000mm $\frac{5}{8}" \times \frac{1}{2}" \times 78\frac{3}{4}"$
------	--

Lenght	3000mm 118 $\frac{1}{8}"$
--------	------------------------------

Internal width	13mm $\frac{1}{2}"$
----------------	------------------------

Cover	PMMA
-------	------

Accessories



TT-73-END-BK



TT-73-MAG

PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER	-	FINISH
TT	-	73	-	3000	-	O	-	BK

TRIM-LESS MUD-IN




Credit photo: Godomo




Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-26-3000 Page 97




Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-27-3000 Page 98



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-28-3000 Page 99



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-29-3000 Page 100



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-33-2000 Page 101



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-34-2000 Page 102



Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-36-2000 Page 103




Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-41-2000 Page 104




Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118

TT-72-2000 Page 105






Power (W/m)	Luminous flux (lm/foot)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118




PRODUCT BUILDER CODE

TT	-	PROFILE	-	LENGTH (inch)	-	LUMEN PACKAGE	-	COLOUR CCT	-	IP	-	VOLTAGE	-	LEAD IN (inch)	-	LEAD OUT (inch)	-	END CAP	-	CLIP	-	PSU
TT	-		-		-		-		-		-		-		-		-		-		-	
						28/6 221 lm/foot 5W/foot		27 2700K		20		12		Hxxxx 12 inchs minimum		empty No lead out		NE No end cap		NC No Clip		n/a No psu
						28/6 H 527 lm/foot 6,25W/foot *24v only		30 3000K		65		24		DCxxxx 12 inchs minimum		Hxxxx 12 inchs minimum		EC With end cap		xC x=QTE		P Plug-in
						28/12 456 lm/foot 9W/foot *24v only		35 3500K								DCxxxx 12 inchs minimum						CV Dimmable
						35/3 45 lm/foot 1,5W/foot		40 4000K														CV-BOX Dimmable with box
						35/6 120 lm/foot 3W/foot		60 6000K														CV67 IP67 psu
						22/15 425 lm/foot 9W/foot *24v only		RE RED														120V No dimmable 120v psu
						50/3 4,5W/foot		GR GREEN														347V No dimmable 347V PSU
						DX/24 DIGITAL DMX *24V only		BL BLUE														010 0-10v PSU
								AM AMBER														
								PK PINK *28/6 only														
								CB CYAN *28/6 only														
								OR ORANGE *28/6 only														
								UV *28/6 only														
								RGB *50/3, 28/6 or 35/6 only														
								RGBWW *50/3 only														
								RGBNW *50/3 only														
								RGBCW *50/3 only														
								RGBCCT *50/3 only														


For a custom color, add at the end of the manufacturer code number COLOR RAL K7. Contact your dealer about the additional cost to a special color.



- Aluminum profile with opal acrylic.
- Designed to be concealed in plaster walls.
- Available in lengths 3000 mm (118¹/₈ ").



Size	13mm x 14mm x 3000mm $\frac{3}{8}" \times \frac{9}{16}" \times 118\frac{1}{8}"$
Lenght	3000 mm 118 ¹ / ₈ "
Internal width	11,1mm $\frac{7}{16}"$
Cover	PC diffused



Accessories



TT-26-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	26	-	3000	-	O


TT-27-3000-O



- Aluminum profile with opal acrylic.
- Designed to be concealed in plaster walls.
- Available in lengths 3000 mm (118¹/₈ ").



Size	13mm x 14mm x 3000mm $\frac{3}{8}" \times \frac{9}{16}" \times 118\frac{1}{8}"$
Lenght	3000 mm $118\frac{1}{8}"$
Internal width	11,1mm $\frac{7}{16}"$
Cover	PC diffused




Accessories




PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	27	-	3000	-	O


TT-28-3000-O



- Aluminum profile with opal acrylic.
- Designed to be concealed in plaster walls.
- Available in lengths 3000 mm ($118\frac{1}{8}$ ").



Size	13mm x 14mm x 3000mm $\frac{3}{8}$ " x $\frac{9}{16}$ " x $118\frac{1}{8}$ "
Lenght	3000 mm $118\frac{1}{8}$ "
Internal width	11,1mm $\frac{7}{16}$ "
Cover	PC diffused



Accessories




TT-28-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	28	-	3000	-	O


TT-29-3000-O



- Aluminum profile with opal acrylic.
- Designed to be concealed in plaster walls.
- Available in lengths 3000 mm (118¹/₈ ").



Size	25mm x 15,5mm x 3000mm $\frac{3}{8}'' \times \frac{5}{8}'' \times 118\frac{1}{8}''$
Lenght	3000 mm $118\frac{1}{8}''$
Internal width	16mm $\frac{5}{8}''$
Cover	PC diffused



Accessories




PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	29	-	3000	-	O


TT-33-2000-O



- Aluminum profile with opal acrylic.
- Designed to be concealed in plaster walls.
- Available in lengths 2000 mm ($78\frac{3}{4}$ ").



Size	25,5mm x 28mm x 2000mm $1" \times 1\frac{1}{8}" \times 78\frac{3}{4}"$
Lenght	2000mm $78\frac{3}{4}"$
Internal width	22,5mm $\frac{7}{8}"$
Cover	PC diffused



Accessories



TT-33-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	33	-	2000	-	O


TT-34-2000-O



- Aluminum profile with opal acrylic.
- Designed to be concealed in plaster walls.
- Available in lengths 2000 mm (78³/₄ ").



Size	25,5mm x 28mm x 2000mm 1" x 1 ¹ / ₈ " x 78 ³ / ₄ "
Lenght	2000mm 78 ³ / ₄ "
Internal width	22,5mm 7/8"
Cover	PC diffused



Accessories



TT-34-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	34	-	2000	-	O


TT-36-2000-O



- Aluminum profile with opal acrylic.
- Designed to be concealed in plaster walls.
- Available in lengths 2000 mm ($78\frac{3}{4}$ ").



Size	98mm x 15mm x 2000mm $3\frac{7}{8}$ " x $\frac{5}{8}$ " x $78\frac{3}{4}$ "
Lenght	2000mm $78\frac{3}{4}$ "
Internal width	13,8mm $\frac{9}{16}$ "
Cover	PC diffused
Finish	White



Accessories



TT-36-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	36	-	2000	-	O


TT-41-2000-O




- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat the LED strips.
- Available in lengths 2000 mm ($78\frac{3}{4}$ ").



Size	99,4mm x 15,4mm x 2000mm $3\frac{15}{16}$ " x $\frac{5}{8}$ " x $78\frac{3}{4}$ "
Lenght	2000mm $78\frac{3}{4}$ "
Internal width	13,8mm $\frac{9}{16}$ "
Cover	PC diffused
Finish	White




Accessories




PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	41	-	2000	-	O


TT-72-2000-0



- Aluminum profile with opal acrylic.
- Designed to be concealed in plaster walls.
- Available in lengths 2000 mm ($78\frac{3}{4}$ ").



Size	80mm x 80mm x 2000mm $3\frac{3}{16}$ " x $3\frac{3}{16}$ " x $78\frac{3}{4}$ "
Lenght	2000mm $78\frac{3}{4}$ "
Internal width	10,3mm X 2 $\frac{7}{16}$ "
Cover	PC diffused
Finish	White




Accessories




PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	72	-	2000	-	0

TT-78-2000-O




- Designed to cover and dissipate heat the LED strips.
- Available in lengths 2000 mm ($78\frac{3}{4}$ ").



Size	43,9mm x 18,5mm x 2000mm $1\frac{3}{4}$ " x $\frac{3}{4}$ " x $78\frac{3}{4}$ "
Lenght	2000mm $78\frac{3}{4}$ "
Internal width	13,9mm $\frac{9}{16}$ "
Cover	PC diffused
Finish	White

Accessories



PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	78	-	2000	-	O

TRIM-LESS TILES



Credit photo: Godomo


TITANIUM

TECHNOLOGY




TT-11-2000 Page 110

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118




TT-43-2000 Page 111

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-44-2000 Page 112

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-45-2000 Page 113

Power (W/m)	Luminous flux (lm/feet)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



PRODUCT BUILDER CODE

TT	-	PROFILE	-	LENGTH (inch)	-	LUMEN PACKAGE	-	COLOUR CCT	-	IP	-	VOLTAGE	-	LEAD IN (inch)	-	LEAD OUT (inch)	-	END CAP	-	CLIP	-	PSU
TT	-		-		-		-		-		-		-		-		-		-		-	

28/6
221 lm/feet
5W/feet

28/6 H
527 lm/feet
6,25W/feet
*24v only

28/12
456 lm/feet
9W/feet
*24v only

35/3
45 lm/feet
1,5W/feet

35/6
120 lm/feet
3W/feet

22/15
425 lm/feet
9W/feet
*24v only

50/3
4,5W/feet

DX/24
DIGITAL DMX
*24V only

27

2700K

30

3000K

35

3500K

40

4000K

60

6000K

RE

RED

GR

GREEN

BL

BLUE

AM

AMBER

PK

PINK

*28/6 only

CB

CYAN

*28/6 only

OR

ORANGE

*28/6 only

UV

*28/6 only

RGB

*50/3, 28/6 or

35/6 only

RGBWW

*50/3 only

RGBNW

*50/3 only

RGBCW

*50/3 only

RGBCCT

*50/3 only

20

2000K

65

6500K

12

1200K

24

2400K

Hxxxx
12 inches
minimum

DCxxxx
12 inches
minimum

empty
No lead out

Hxxxx
12 inches
minimum

DCxxxx
12 inches
minimum

NE
No end
cap

EC
With end
cap

NC
No Clip

xC
x=OTE

n/a
No psu

P
Plug-in

CV
Dimmable

CV-BOX
Dimmable with box

CV67
IP67 psu


120V
No dimmable
120v psu

347V
No dimmable
347v PSU


010
0-10v PSU

For a custom color, add at the end of the manufacturer code number COLOR RAL K7. Contact your dealer about the additional cost to a special color.


TT-11-2000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2000 mm (78³/₄").



Size	41mm x 13mm x 2000mm 1 ⁵ / ₈ " x 1 ¹ / ₂ " x 78 ³ / ₄ "
Lenght	2000mm 78 ³ / ₄ "
Internal width	12,3mm 1 ¹ / ₂ "
Cover	PC diffused



Accessories




PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	11	-	2000	-	O


TT-43-2000-O



- Aluminum profile with opal acrylic.
- Designed to conceal between ceramic wall tiles.
- Available in lengths 2000 mm ($78\frac{3}{4}$ ").



Size	33mm x 11mm x 2000mm $1\frac{5}{16}$ " x $\frac{7}{16}$ " x $78\frac{3}{4}$ "
Lenght	2000mm $78\frac{3}{4}$ "
Internal width	10,5mm $\frac{7}{16}$ "
Cover	PC diffused




Accessories




PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	43	-	2000	-	O


TT-44-2000-O



- Aluminum profile with opal acrylic.
- Designed to conceal between ceramic wall tiles.
- Available in lengths 2000 mm (78³/₄ ").



Size	40mm x 40mm x 2000mm 1 ⁹ / ₁₆ " x 1 ⁹ / ₁₆ " x 78 ³ / ₄ "
Lenght	2000mm 78 ³ / ₄ "
Internal width	10,5mm 7/ ₁₆ "
Cover	PC diffused



Accessories



TT-44-END


PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	44	-	2000	-	O


TT-45-2000-O




- Aluminum profile with opal acrylic.
- Designed to conceal between ceramic wall tiles.
- Available in lengths 2000 mm (78³/₄ ").



Size	38mm x 38mm x 2000mm 1 ¹ / ₂ " x 1 ¹ / ₂ " x 78 ³ / ₄ "
Lenght	2000mm 78 ³ / ₄ "
Internal width	10,5mm 7/ ₁₆ "
Cover	PC diffused



Accessories



TT-45-END

PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	45	-	2000	-	O

BOTTOM WALL





Credit photo: Cuisines Simard


TITANIUM TECHNOLOGY - 2025 115

TT-30-2000-O

- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2000 mm (78¾").



Size	80mm x 16mm x 2000mm 3 ¹ / ₈ " x 5 ⁵ / ₈ " x 78 ³ / ₄ "
Lenght	2000mm 78 ³ / ₄ "
Internal width	10,3mm 3 ³ / ₈ "
Cover	PC diffused



Accessories





PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	30	-	2000	-	O


TT-51-2000-O

- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2000 mm (78³/₄").



Size	80mm x 15mm x 2000mm 3 ¹ / ₈ " x 9 ⁹ / ₁₆ " x 78 ³ / ₄ "
Lenght	2000mm 78 ³ / ₄ "
Internal width	10,4mm 7 ⁷ / ₁₆ "
Cover	PC diffused

Accessories



TT-51-END



TT-51-EXT

PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	51	-	2000	-	O

CLOSET




Credit photo: Godomo


TT-35-2000-O



- Aluminum profile with opal acrylic.
- Designed for wardrobes.
- Available in lengths 2000 mm (78³/₄ ").



Size	27,5mm x 33mm x 2000mm 1 ¹ / ₁₆ " x 1 ⁵ / ₁₆ " x 78 ³ / ₄ "
Lenght	2000mm 78 ³ / ₄ "
Internal width	12mm 1/2"
Cover	PC diffused



Accessories



PRODUCT CODE


TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	35	-	2000	-	O

STAIRS




TT-42-2000-O

- Aluminum profile with opal acrylic.
- Designed for stairs with non-slip rubber band.
- Available in lengths 2000 mm (78³/₄ ").



Size	65mm x 27mm x 2000mm 2 ⁹ / ₁₆ " x 1 ¹ / ₁₆ " x 78 ³ / ₄ "
Length	2000mm 78 ³ / ₄ "
Internal width	12,9mm 1/2"
Cover	PC diffused
Finish	Black



Accessories



PRODUCT CODE


TT	-	MODEL	-	LENGTH (mm)	-	COVER
TT	-	42	-	2000	-	O

TRIM-LESS CONCRETE




Credit photo: Maison Profab

TT-12-3000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 3000 mm (118¹/₈"").



Size	26mm x 26mm x 3000mm 1" x 1" x 118 ¹ / ₈ "
Lenght	3000mm 118 ¹ / ₈ "
Internal width	12mm ¹ / ₂ "
Cover	PC diffused

Accessories



TT-12-END

PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	12	-	3000	-	O

SUSPENDED CEILING




Credit photo: Godomo


TT-67-2000-O



- Aluminum profile with opal acrylic.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 2000 mm ($78\frac{3}{4}$ ").



Size	45,7mm x 50,1mm x 2000mm $1\frac{13}{16}$ " x 2" x $78\frac{3}{4}$ "
Lenght	2000mm $78\frac{3}{4}$ "
Internal width	19,9mm $\frac{13}{16}$ "
Cover	PC diffused



Accessories



TT-67-END

PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	67	-	2000	-	O

EDGE



Credit photo: Groupe Dallaire



TT-70-2000 Page 128

Power (W/m)	Luminous flux (lm/foot)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118



TT-71-2000 Page 129

Power (W/m)	Luminous flux (lm/foot)	CRI	CCT (Kelvin)	Length (inch)
5,9 ~ 34	38 ~ 600	90	2700 ~ 6000	1 ~ 118





PRODUCT BUILDER CODE


TT	PROFILE	LENGTH (inch)	LUMEN PACKAGE	CLOUR CCT	IP	VOLTAGE	LEAD IN (inch)	LEAD OUT (inch)	END CAP	CLIP	PSU
TT											
			28/6 221 lm/foot 5W/foot	27 2700K	20	12	Hxxxx 12 inchs minimum	empty No lead out	NE No end cap	NC No Clip	n/a No psu
			28/6 H 527 lm/foot 6,25W/foot *24v only	30 3000K	65	24	DCxxxx 12 inchs minimum	Hxxxx 12 inchs minimum	EC With end cap	xC x=QTE	P Plug-in
			28/12 456 lm/foot 9W/foot *24v only	35 3500K			DCxxxx 12 inchs minimum				CV Dimmable
			35/3 45 lm/foot 1,5W/foot	40 4000K							CV-BOX Dimmable with box
			35/6 120 lm/foot 3W/foot	60 6000K							CV67 IP67 psu
			22/15 425 lm/foot 9W/foot *24v only	RE RED							120V No dimmable 120v psu
			50/3 4,5W/foot	GR GREEN							347V No dimmable 347V PSU
			DX/24 DIGITAL DMX *24V only	BL BLUE							010 0-10v PSU
				AM AMBER							
				PK PINK *28/6 only							
				CB CYAN *28/6 only							
				OR ORANGE *28/6 only							
				UV *28/6 only							
				RGB *50/3, 28/6 or 35/6 only							
				RGBWW *50/3 only							
				RGBNW *50/3 only							
				RGBCW *50/3 only							
				RGBCCT *50/3 only							

For a custom color, add at the end of the manufacturer code number COLOR RAL K7. Contact your dealer about the additional cost to a special color.


TT-70-2000-O



Size	2000 mm x 91 mm x 49 mm 78 ³ / ₄ " x 3 ¹ / ₂ " x 1 ⁷ / ₈ "
Lenght	2000 mm 78 ³ / ₄ "
Internal width	13 mm 1 ¹ / ₂ "
Cover	PC diffused




Accessories



PRODUCT CODE

TT	-	MODEL	-	LENGHT (mm)	-	COVER
TT	-	70	-	2000	-	O

TT-71-2000-O




Size 73,2mm x 30,2mm x 2000mm
2⁷/₈" x 1³/₁₆" x 78³/₄"


Lenght 2000mm
78³/₄"

Internal width 13,3mm
9/₁₆"

Cover Semi-clear PMMA



Accessories




PRODUCT CODE

TT - MODEL - LENGHT (mm) - COVER

TT - 71 - 2000 - O

FLEX




Credit photo: Godomo


TT	-	PROFILE	-	LENGTH (inch)	-	LUMEN PACKAGE	-	COLOUR CCT	-	IP	-	VOLTAGE	-	LEAD IN (inch)	-	LEAD OUT (inch)	-	END CAP	-	CLIP	-	PSU
----	---	---------	---	------------------	---	------------------	---	---------------	---	----	---	---------	---	-------------------	---	-----------------------	---	------------	---	------	---	-----

For a custom color, add at the end of the manufacturer code number COLOR RAL K7. Contact your dealer about the additional cost to a special color.


TT-FLEX-01



- Silicone profile.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 5000 mm (197").



Size	10,4mm x 18mm x 5000mm 7/16" x 11/16" x 197"
Lenght	5000mm 197"
Internal width	11,2mm 7/16"
Cover	White silicone



Accessories



TT-FLEX-01-CLIP



TT-FLEX-01-AC




TT-FLEX-01-END

PRODUCT CODE			
TT	-	TYPE	- MODEL
TT	-	FLEX	- 01


TT-FLEX-02



- Silicone profile.
- Designed to cover and dissipate heat of the LED strips.
- Available in lengths 5000 mm (197").




Size	16 mm x 16 mm x 5000 mm $\frac{5}{8}'' \times \frac{5}{8}'' \times 197''$
Lenght	5000mm 197"
Internal width	11,2mm $\frac{7}{16}''$
Cover	White silicone




Accessories



TT-FLEX-02-CLIP



TT-FLEX-02-AC



TT-FLEX-02-END

PRODUCT CODE

TT	-	TYPE	-	MODEL
TT	-	FLEX	-	02

LIMITED ONE (1) YEAR WARRANTY

Titanium Technology offers this limited warranty for one (1) year from the date of purchase of this Titanium Technology product (hereafter : the «Product»). A list of all the Titanium Technology products covered by this limited warranty is given at the end of this document.

This limited warranty is valid only for the Product and it may not be transferred.

The present limited warranty is not meant to exclude, restrict, limit or modify the legal warranty given by law to the purchaser of the Product.

This is a quality Product. It was made and selected with care. If the Product contains a manufacturing defect or if one or more parts of the Product is defective, the retailer commits to replace or repair, at its sole discretion, the defective part of parts without charge under the following cumulative conditions : 1) the purchaser must contact the retail store where the Product was purchased; 2) the purchaser must return the defective part of parts or the Product to the retailer; 3) the purchaser must provide the retailer the invoice as proof of purchase and date of purchase of the Product; 4) the purchaser must supply the Product identification information, including the serial number or the model number; and 5) the period of one (1) year covered by this limited warranty must not be expired. If the retailer decides to replace the defective part or parts, the replacement part or parts would be new or reconditioned, equivalent to new parts.

EXCLUSIONS AND LIMITATIONS OF THE LIMITED WARRANTY

This limited warranty is not applicable :

1. to consumable parts;
2. to normal wear;
3. when the Product is used for purposes other than those determined by the manufacturer;
4. when the Product is not installed by a qualified electrician when electrical work is required;
5. when the serial number or other identification information or the Product is erased or withdrawn;
6. to damages that are only aesthetic and do not affect the normal use of the Product, including scatches, bumps etc.;
7. to labour costs such as installation, de-installation or shipping of the Product which must be paid by the purchaser;
8. to service call costs, when the service call is made while the warranty is not valid;
9. when the damages, defects, faults or other problems arise from :
 - a. an abnormal use of the Product;
 - b. an inadequate maintenance of the Product;
 - c. a faulty installation of the Product or an installation that is not in accordance with the installation guide (if one is provided);
 - d. a modification, a repair or dismantling of the Product by a person not authorized by the retailer or the manufacturer;
 - e. the transportation by the purchaser, his employee, officer or representative;
 - f. a negligence by the purchaser, his employee, officer or representative;
 - g. an accident;
 - h. a case of force majeure (are considered force majeure : nature disasters, lightning, flood, fire etc.);
 - i. any event that is not caused by the Product itself.

In no circumstance can the manufacturer or retailer be held responsible for any extraordinary, special, indirect, accessory or consecutive damages resulting from the use of or the incapacity to use the Product. Their responsibility is limited to the sale price of the Product as indicated on the notice and paid by the purchaser at the time of purchase. It is understood that this is not meant to limit, restrict or exclude the protection given by the legal warranty.

FRENCH VERSION VS ENGLISH VERSION

In case of discrepancy between the French and the English versions of the text of this limited warranty, the French version shall prevail.

MODIFICATIONS

The present warranty text is subject to change at any time.

List of Titanium Technology products covered under this limited warranty :


- | | | |
|--------------------------|--------------------------|-----------------------|
| 1) Nicolaudie Controller | 5) TT-CAB-XX | 9) TT-WiFi |
| 2) LTECH Controller | 6) TT-DMX-XX | 10) Aluminium profile |
| 3) TT-ACC-XX | 7) TT-PSU-IP20 / PLUG-IN | 11) TT-Y-XX |
| 4) TT-AMP-XX | 8) TT-U-XX | |

Note : This product list may not be up to date. Please refer to the product itself (including the package or installation guide) to make sure it is covered by this limited warranty.



TITANIUM

TECHNOLOGY



TITANIUM TECHNOLOGY
2323, boulevard Versant Nord #111
Québec, QC
G1N 4P4 CANADA
Toll free (866)-476-8115
www.titaniumtechnology.com
sales@titaniumtechnology.com
www.facebook.com/titaniumtechnologie

TITANIUM TECHNOLOGY USA
NEWARK DE 19713
Toll free (866)-476-8115 ext.203
www.titaniumtechnology.com
sales@titaniumtechnology.com
www.facebook.com/titaniumtechnologie