


TITANIUM

TECHNOLOGIE

TT-2835-L1200



- Ruban DEL SMD2835 en rouleau de 5 mètres.



Tension	24vDC	
DEL/m	240 / m	
Puissance	30,4 w / m 9,26 w / pied 152 w / rouleau	
Ampérage	1,27 A / m 0,39 A / pied 6,34 A / rouleau	
Lumens	27K - 448 lm / pied 30K - 456 lm / pied 35K - 452 lm / pied 40K - 422 lm / pied 60K - 384 lm / pied	- 55 lm / w - 64 lm / w 57 lm / w
Angle	120°	
Dimension	IP20	10mm x 2,3mm x 5000mm $\frac{3}{8}$ " x $\frac{1}{8}$ " x 196 $\frac{7}{8}$ "
	IP65	10mm x 3,2mm x 5000mm $\frac{3}{8}$ " x $\frac{1}{8}$ " x 196 $\frac{7}{8}$ "
	IP67	13mm x 5mm x 5000mm $\frac{1}{2}$ " x $\frac{3}{16}$ " x 196 $\frac{7}{8}$ "
Ligne de coupe	25 mm 1"	
Finition	Blanc	
Gradable	Oui	
Couleur DEL	27K - Blanc chaud 2700K 30K - Blanc chaud 3000K 35K - Blanc neutre 3500K 40K - Blanc neutre 4000K 60K - Blanc froid 6000K R - Rouge G - Vert B - Bleu A - Ambre	
Temp. fonctionnement	-40°C ~ 70°C	
IP	20, 65, 67	

CODE PRODUIT

TT	SMD	DEL PAR ROULEAU	IP	COULEUR DEL	TENSION
TT	2835	L1200	20	27K	24V
TT	2835	L1200			24V

IES Indoor Report

Photometric Filename:TT-2835-L1200-6000K-1-NO LENS.IES

Indoor Luminaire Photometric Data

Description Information

Luminaire Name: TT-2835-L1200-6000k-1-NO-lens	Luminaire Catalog:	Test ID:
Lamp Name: TT-2835-L1200-6000k-1-NO-lens	Lamp Catalog: 2835	Test Date: 2021/03/23
Manufacture: TITANIUM TECHNOLOGIE	ShieldingAngle(°):	Test Machine: GON-2000
Test Lab:	Frequency(Hz):	Luminaire CCT(K):
Luminaire Size(W*L*H): 0.120*0.304*0.060	Lighting Area(m2): 0.055	Luminaire Weight(kg): 0.100
Test System: C, γ	Test Step: C=45.0 γ =1.0	Temperature(°C): 25
		Humidity(%):

Character Parameter

Lamp Speciality Parameter	
Lamp Rated Lumens(lm): 448.000	Lamp Number in Luminaire: 1
Lamp Norminal Power(W):	Lamp Rated Voltage(V):
Lamp Tested Power(W): 6.774	Lamp Tested Voltage(V): 24.5
Lamp Tested Current(A): 0.276	Lamp Tested PF:
Lamp Size(W*L*H): 0.120*0.304*0.060	
Luminaire Speciality	
Luminaire Lumens(lm): 383.839	Beam Angle(10%Imax): 104.8
Luminaire Efficiency: 85.68%	Left=-51.2 Right=53.6
Luminaire EER(lm/W): 56.663	Field Angle(10%Imax): 114.5
Muximum Cand.(cd): 158.372	Spacing Criteria S/MH(C0_180): 1.330
Max Cd. Angle(°): C=180.0 γ =8.0	Spacing Criteria S/MH(C90_270): 1.296
Downward Lumens(lm): 383.839	CIE Type: Semi-Direct
Upward Lumens(lm): 0.000	ErP ϕ use(120deg): 356.015lm
Downward Total Efficiency%: 100.00	IRF(%): 106.673
Upward Total Efficiency%: 0.00	

IES Indoor Report

Photometric Filename: TT-2835-L1200-6000K-1-NO LENS.IES

2D Light Intensity Distribution Curve





Plane [50%Ang.] [10%Ang.]

C180.0: 104.8 114.5

C0.0: 104.8 114.5

C90.0: 113.2 149.0

Polar Graph



C Plane: C180.0_360.0 ——— C0.0_180.0 ———


γ Cone: γ8.0 ———

C90.0_270.0 ———

IES Indoor Report

Photometric Filename: TT-2835-L1200-6000K-1-NO LENS.IES

Rectangle ISO Light Intensity Curve




Curves: 90% — 80% — 70% — 60% — 50% — 40% — 30% — 20% — 10% —

Maximum Light Intensity(cd): 158.37 Maximum Cd. Angles: H-8.0 V0.0

IES Indoor Report

Photometric Filename: TT-2835-L1200-6000K-1-NO LENS.IES


Plane ISO-Illuminance Curve




IES Indoor Report

Photometric Filename: TT-2835-L1200-6000K-1-NO LENS.IES

Space ISO Illuminance Curve



Illuminance-Distance Curve



Beam Angle:104.8

IES Indoor Report

Photometric Filename:TT-2835-L1200-6000K-1-NO LENS.IES

Indoor Luminance Limiting Curve


Glare Grade Table

GI	Quality	Using Illuminance							
		a	b	c	d	e	f	g	h
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300
		a	b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	2770	2518	893	0	0	0	0	0	0
C90	2990	2953	2906	2817	2644	2351	1745	0	0

Luminance Limiting Curve




Luminous Size: Length(m)=0.304 Width(m)=0.120 Height(m)=0.060 Area(m²)=0.054720
 Luminous Type: Without Luminous Side
 Luminous Curves: C0-C180 Color: — C90-C270 Color: —

IES Indoor Report

Photometric Filename: TT-2835-L1200-6000K-1-NO LENS.IES

Indoor Budgetary Estimate Table



Parameters1: Rhocc = 0.7 Rhow = 0.5 Rhofc = 0.2 LLF = 0.8
 Parameters2: Rhocc = 0.5 Rhow = 0.3 Rhofc = 0.2 LLF = 0.8
 Average Illuminance(lx): 100 Cavity Height: H1(m) = 2